

SUS304・SUS430 パンチングメタル

SUS304の表面肌=BA (板厚0.3t・3tは2B)

サイズ	孔径 φ	×	ピッチ P	特記	開口率 %	板厚									
						0.3	0.4	0.5	0.6	0.8	1.0	1.2	1.5	2.0	3.0
1000 × 2000 (1'×2')	○	×	+		32.0	●	●	●	●	●	●	●	●		
	0.5	×	1.09		19.0	●	●								
	0.8	×	1.55		24.2				●						
	1	×	2		22.6			●	●	●	●				
	1.5	×	3		22.6			●		●	●				
	2	×	3		40.2						●				
	2	×	3.5		29.6				●	●	●	●	●		
	2.5	×	4		35.4						●				
	3	×	4		50.9			●		●	●				
	3	×	5		32.6		●	●	●	●	●	●	●	●	●
	4	×	5		57.9						●				
	4	×	7		29.6				●	●	●	●	●	●	
	5	×	7		46.2						●				
	5	×	8		35.4			●	●	●	●	●	●	●	●
	6	×	8		50.9					●	●		●		
	6	×	9		40.2				●	●	●	●	●	●	
	8	×	10		57.9				●	●	●	●			
	8	×	12		40.2						●	●	●	●	●
	10	×	15		40.2					●	●	●	●	●	●
	12	×	18		40.2							●	●		
	15	×	20		50.9							●	●		
	16	×	21		53.0	(この規格は別メーカーの製品になります)						●	●		
	20	×	30		40.2								●	●	
3角	×	5	並列	36.0						●					
8角	×	8	並列	64.0						●					
長孔3	×	12		39.3											
長孔3	×	20		39.7				●							
10	×	15	HL SPV	40.2								●			
<b>SUS430</b>															
	3	×	5		40.2					●	●				
	5	×	8		40.2					●	●				

1219 × 2438 (4'×8')	3	×	5		32.6					●	●	●	●		
	5	×	8		35.4					●	●	●	●	●	
	6	×	9		40.2							●			
	8	×	12		40.2	(この規格は別メーカーの製品になります)						●			
	10	×	15		40.2					●	●	●	●	●	
	10	×	15	HL SPV	40.2							●			

■パンチングメタル各部の名称

