

SUS304 平角棒

○：スリットの酸洗肌

単位：mm

サイズ	長さ	コールド	H L	#400	ホット		
					熱間	スリット	
厚さ×幅							
2	× 6	2,000	●				
		2,000	●				
	× 8	2,000	●				
		2,000	●				
		3,000	●				
	× 10	2,000	●				
		2,000	●				
		4,000	●	●			●
	× 12	4,000	●				
	× 15	4,000	●	●			●
	× 20	4,000	●	●			●
	× 25	4,000	●	●			●
	× 30	4,000	●	●			●
	× 32	4,000	●	●			●
	× 35	4,000					●
	× 38	4,000	●				●
	× 40	4,000	●	●			●
× 45	4,000	●	●			●	
× 50	4,000	●	●			●	
3	× 5	2,000	●				
		3,000	●				
	× 6	3,000	●				
		4,000	●				
	× 7	3,000	●				
		4,000	●				
	× 8	3,000	●				
		4,000	●				
	× 9	3,000	●				
		4,000	●				
	× 10	4,000	●	●			●
	× 12	4,000	●	●		○	●
	× 13	4,000	●	●			●
	× 15	4,000	●	●	●	○	●
	× 16	4,000	●	●			●
	× 19	4,000	●	●		○	●
	× 20	4,000	●	●	●	○	●
	× 22	4,000	●	●			●
	× 25	4,000	●	●	●	○	●
	× 30	4,000	●	●	●	○	●
	× 32	4,000	●	●	●	○	●
	× 35	4,000	●	●		○	●
	× 38	4,000	●	●	●	○	●
	× 40	4,000	●	●	●	○	●
	× 42	4,000	●	●			●
	× 45	4,000	●	●		○	●
	× 48	4,000	●	●			
× 50	4,000	●	●	●	○	●	
× 60	4,000	●	●	●	○	●	
× 65	4,000	●	●		○	●	
× 75	4,000	●	●			●	

サイズ	長さ	コールド	H L	#400	ホット		
					熱間	スリット	
厚さ×幅							
3	× 90	4,000	●				
		4,000	●	●	●		●
	× 110	4,000	●				
		4,000	●				
	× 125	4,000	●				
		4,000	●				
	× 130	4,000	●				
		4,000	●				
	× 140	4,000	●				
		4,000	●				
	4	× 9	4,000	●			
4,000			●	●			
× 11		4,000	●	●			●
		4,000	●				
× 13		4,000	●	●			●
		4,000	●	●	●	●	●
× 16		4,000	●	●		●	●
		4,000	●				
× 19		4,000	●	●		●	●
		4,000	●	●	●	●	●
× 22		4,000	●	●		●	●
		4,000	●	●	●	●	●
× 30		4,000	●	●	●	●	●
		4,000	●	●		●	●
× 35		4,000	●	●		●	●
		4,000	●	●	●	●	●
× 40		4,000	●	●	●	●	●
		4,000	●	●		●	●
× 50		4,000	●	●	●	●	●
	4,000	●	●	●	●	●	
× 60	4,000	●	●	●	●	●	
	4,000	●	●	●	●	●	
× 75	4,000	●	●	●	●	●	
	4,000	●	●				
5	× 8	4,000	●				
		4,000	●				
	× 10	4,000	●	●			
		4,000	●	●			
	× 15	4,000	●	●	●	●	●
		4,000	●	●			●
	× 19	4,000	●	●		●	●
		4,000	●	●	●	●	●
	× 22	4,000	●	●		●	●
		4,000	●	●	●	●	●
	× 30	4,000	●	●	●	●	●
4,000		●	●	●	●	●	
× 35	4,000	●	●		●	●	
	4,000	●	●	●	●	●	
× 38	4,000	●	●	●	●	●	
	4,000	●	●				

SUS304 平角棒

単位 : mm

サイズ		長さ	コールド	H L	# 4 0 0	ホット	
厚さ×幅						熱間	スリット
5	× 40	4,000	●	●	●	●	●
	× 45	4,000				●	●
	× 50	4,000	●	●	●	●	●
	× 60	4,000	●	●	●	●	●
	× 65	4,000	●	●	●	●	●
	× 75	4,000	●	●	●	●	●
	× 90	4,000	●	●		●	●
	× 100	4,000	●	●	●	●	●
	× 130	4,000	●				
	× 150	4,000	●				
	6	× 9	4,000	●			
× 10		4,000	●	●			
× 12		4,000	●	●			
× 13		4,000	●	●			
× 15		4,000	●	●	●	●	●
× 16		4,000	●	●			●
× 18		4,000	●	●			
× 19		4,000	●	●		●	●
× 20		4,000	●	●	●	●	●
× 22		4,000	●	●		●	●
× 25		4,000	●	●	●	●	●
		5,000				●	
		6,000				●	
× 30		4,000	●	●	●	●	●
		5,000				●	
		6,000		●		●	
× 32		4,000	●	●	●	●	●
		5,000				●	
		6,000				●	
× 35		4,000	●	●		●	●
× 38		4,000	●	●	●	●	●
		5,000				●	
		6,000		●		●	●
× 40		4,000	●	●	●	●	●
		5,000				●	
		6,000		●		●	
× 42		4,000	●	●			
× 45		4,000	●	●	●	●	●
× 48		4,000	●	●		●	●
× 50		4,000	●	●	●	●	●
		5,000				●	
		6,000	●	●		●	●
× 60		4,000	●	●	●	●	●
× 65	4,000	●	●	●	●	●	
	5,000				●		
	6,000		●		●	●	
× 70	4,000	●	●		●	●	
× 75	4,000	●	●	●	●	●	

サイズ		長さ	コールド	H L	# 4 0 0	ホット	
厚さ×幅						熱間	スリット
6	× 75	5,000				●	●
		6,000		●		●	●
	× 90	4,000	●	●	●	●	●
		× 100	4,000	●	●	●	●
		5,000				●	
		6,000		●		●	●
	× 110	4,000	●	●			●
	× 120	4,000	●	●			●
	× 125	4,000	●	●			●
	× 130	4,000	●	●			●
	× 140	4,000	●	●			●
× 150	4,000	●	●			●	
7	× 20	4,000				●	
8	× 10	4,000	●	●			
	× 16	4,000	●	●			●
	× 25	4,000					●
	× 30	4,000					●
	× 32	4,000	●	●	●	●	
	× 35	4,000					●
	× 38	4,000	●	●			●
	× 40	4,000					●
	× 45	4,000					●
	× 50	4,000	●	●			●
	× 65	4,000					●
× 75	4,000					●	
× 100	4,000					●	
9	× 13	4,000	●	●		●	
	× 15	4,000	●	●	●	●	
	× 16	4,000	●	●			●
	× 19	4,000	●	●			●
	× 20	4,000	●	●	●	●	●
	× 22	4,000	●	●			●
	× 25	4,000	●	●	●	●	●
		6,000	●	●			
	× 30	4,000	●	●	●	●	●
		6,000	●	●			
	× 32	4,000	●	●	●	●	●
		5,000				●	
		6,000	●	●			●
	× 35	4,000	●	●			●
	× 38	4,000	●	●	●	●	●
		5,000				●	
	× 40	4,000	●	●	●	●	●
× 45	4,000	●				●	
× 50	4,000	●	●	●	●	●	

SUS304 平角棒

単位 : mm

サイズ		長さ	コールド	H L	#400	ホット	
厚さ×幅						熱間	スリット
9	× 50	5,000				●	
		6,000	●	●		●	●
	× 55	4,000				●	
	× 60	4,000	●	●	●	●	●
	× 65	4,000	●	●	●	●	●
		5,000				●	
		6,000	●	●		●	●
	× 75	4,000	●	●	●	●	●
		5,000				●	
		6,000	●	●		●	●
	× 90	4,000	●	●		●	●
		5,000				●	
		6,000				●	
	× 100	4,000	●	●	●	●	●
		5,000				●	
		6,000	●	●		●	●
	× 125	4,000	●	●		●	
		5,000				●	
		6,000				●	
	× 150	4,000	●	●		●	
		5,000				●	
		6,000				●	
	× 200	4,000	●	●		●	
		5,000				●	
	× 250	4,000	●	●		●	
		5,000				●	
	× 300	4,000	●			●	
		5,000				●	
10	× 15	4,000	●	●	●	●	
		5,000				●	
	× 19	4,000	●	●		●	
	× 20	4,000	●	●	●	●	
	× 25	4,000	●	●	●	●	
	× 30	4,000	●	●	●	●	
	× 32	4,000	●	●	●	●	
	× 35	4,000				●	
	× 38	4,000	●	●	●	●	
	× 40	4,000	●	●	●	●	
	× 45	4,000				●	
	× 50	4,000	●	●	●	●	
		5,000				●	
		6,000	●			●	
	× 60	4,000				●	
		5,000				●	
	× 65	4,000	●	●	●	●	
		6,000	●			●	
	× 75	4,000	●	●		●	
		6,000	●			●	
	× 100	4,000	●	●	●	●	
		5,000				●	
		6,000	●			●	
	× 125	4,000	●	●		●	
		5,000				●	
	× 150	4,000	●	●		●	
		5,000				●	

サイズ		長さ	コールド	H L	#400	ホット	
厚さ×幅						熱間	スリット
10	× 200	4,000	●	●		●	
		× 250	4,000	●	●		●
		× 300	4,000				●
12	× 14	4,000	●				
		× 15	4,000				●
	× 16	4,000	●	●			
		× 19	4,000	●	●		●
	× 20	4,000	●	●	●	●	
		× 25	4,000	●	●	●	●
	× 30	4,000	●	●	●	●	
		6,000	●				
	× 32	4,000	●	●	●	●	
		6,000	●	●			
	× 35	4,000	●	●			●
		× 38	4,000	●	●	●	●
	5,000						●
	6,000	●	●		●		
	× 40	4,000	●	●	●	●	
		6,000	●	●			
× 45	4,000					●	
	× 50	4,000	●	●	●	●	
5,000						●	
6,000	●	●		●			
× 65	4,000	●	●	●	●		
	5,000					●	
	6,000	●	●		●		
× 70	4,000					●	
	× 75	4,000	●	●	●	●	
5,000						●	
6,000	●	●		●			
× 90	4,000	●	●			●	
	× 100	4,000	●	●	●	●	
		5,000					●
6,000	●	●		●			
× 125	4,000	●	●			●	
	5,000					●	
	6,000					●	
× 150	4,000	●	●			●	
	5,000					●	
	6,000					●	
× 200	4,000	●	●			●	
	× 250	4,000	●	●		●	
× 300	4,000	●				●	
	5,000					●	
16	× 19	4,000	●	●			
		× 20	4,000	●	●	●	●
	× 25	4,000	●	●	●	●	
		× 30	4,000				●

SUS304 平角棒

単位 : mm

サイズ		長さ	コールド	H L	#400	ホット		
厚さ×幅						熱間	スリット	
16	× 32	4,000	●	●	●	●		
	× 35	4,000				●		
	× 38	4,000	●	●	●	●		
	× 40	4,000	●	●	●	●		
	× 45	4,000				●		
	× 50	4,000	●	●	●	●		
	× 50	5,000				●		
		6,000	●			●		
× 65	4,000	●	●		●			
	5,000				●			
	6,000	●			●			
× 75	4,000	●	●		●			
	5,000				●			
	6,000	●			●			
× 90	4,000				●			
	5,000	●	●		●			
	6,000	●			●			
× 100	4,000	●	●		●			
	5,000				●			
	6,000	●			●			
× 125	4,000	●	●		●			
	5,000				●			
	6,000				●			
× 150	4,000	●	●		●			
	5,000				●			
	6,000				●			
× 200	4,000	●	●		●			
× 250	4,000	●	●		●			
× 300	4,000	●			●			
19	× 25	4,000	●	●	●	●		
	× 30	4,000				●		
	× 32	4,000	●	●	●	●		
	× 35	4,000				●		
	× 38	4,000	●	●	●	●		
	× 40	4,000				●		
	× 45	4,000				●		
	× 50	4,000	●	●	●	●		
		5,000				●		
		6,000				●		
	× 55	4,000				●		
		5,000				●		
		6,000				●		
	× 65	4,000	●	●		●		
		5,000				●		
		6,000				●		
	× 75	4,000	●	●		●		
		5,000				●		
		6,000				●		
× 90	4,000				●			
	5,000	●	●		●			
	6,000	●			●			
× 100	4,000	●	●		●			
	5,000				●			
	6,000				●			
× 125	4,000	●	●		●			
	5,000				●			
	6,000				●			
× 150	4,000	●	●		●			
	5,000				●			
	6,000				●			

サイズ		長さ	コールド	H L	#400	ホット	
厚さ×幅						熱間	スリット
19	× 200	4,000	●	●		●	
	× 250	4,000	●	●		●	
	× 300	4,000	●			●	
20	× 70	4,000				●	
22	× 25	4,000				●	
	× 30	4,000				●	
	× 32	4,000	●			●	
22	× 35	4,000				●	
	× 38	4,000	●			●	
	× 40	4,000				●	
	× 45	4,000				●	
	× 50	4,000	●			●	
	× 65	4,000	●			●	
	× 70	4,000				●	
	× 75	4,000	●			●	
	× 90	4,000				●	
	× 100	4,000	●			●	
	× 125	4,000				●	
	× 150	4,000				●	
	× 200	4,000				●	
× 250	4,000				●		
× 300	4,000				●		
25	× 32	4,000	●			●	
	× 38	4,000	●			●	
	× 40	4,000				●	
	× 45	4,000				●	
	× 50	4,000	●			●	
	× 60	4,000				●	
	× 65	4,000	●			●	
	× 75	4,000	●			●	
	× 100	4,000	●			●	
	× 125	4,000	●			●	
	× 150	4,000	●			●	
	× 200	4,000	●			●	
	× 250	4,000				●	
× 300	4,000				●		
30	× 50	4,000	●			●	
	× 55	4,000	●			●	
	× 60	4,000				●	
	× 65	4,000	●			●	
	× 75	4,000	●			●	
	× 100	4,000	●			●	
	× 125	4,000				●	
	× 150	4,000				●	
	× 200	4,000				●	
	× 250	4,000				●	
× 300	4,000				●		
35	× 50	4,000	●			●	

SUS304 平角棒

サイズ		長さ	コールド	H L	#400	ホット	
厚さ	幅					熱間	スリット
35	× 65	4,000	●			●	
	× 75	4,000	●			●	
	× 100	4,000	●			●	
	× 125	4,000				●	
	× 150	4,000				●	
40	× 50	4,000				●	
	× 65	4,000				●	
	× 75	4,000				●	
	× 100	4,000				●	
	× 125	4,000				●	
× 150	4,000				●		
50	× 65	4,000				●	
	× 75	4,000				●	
	× 100	4,000				●	
	× 125	4,000				●	
	× 150	4,000				●	
60	× 75	4,000				●	
	× 100	4,000				●	
	× 125	4,000				●	
	× 150	4,000				●	
65	× 75	4,000				●	
70	× 100	4,000				●	
	× 125	4,000				●	
	× 150	4,000				●	
80	× 100	4,000				●	
	× 125	4,000				●	
	× 150	4,000				●	
90	× 125	4,000				●	
	× 150	4,000				●	
100	× 125	4,000				●	
	× 150	4,000				●	

SUS304 四角棒

単位 : mm

サイズ		長さ	コールド	H L	#400	HOT
厚さ	幅					
3	× 3	2,000	●			
4	× 4	4,000	●			
5	× 5	4,000	●	●		
6	× 6	4,000	●	●		
7	× 7	4,000	●	●		
8	× 8	4,000	●	●	●	
9	× 9	4,000	●	●	●	
10	× 10	4,000	●	●	●	●
12	× 12	4,000	●	●	●	●
13	× 13	4,000	●	●	●	●
14	× 14	4,000	●	●	●	●
15	× 15	4,000	●	●	●	●
16	× 16	4,000	●	●	●	●
19	× 19	4,000	●	●	●	●
20	× 20	4,000	●	●	●	●
22	× 22	4,000	●	●		●
25	× 25	4,000	●	●	●	●
26	× 26	4,000	●			
28	× 28	4,000	●	●		●
30	× 30	4,000	●	●		●
32	× 32	4,000	●	●		●
36	× 36	4,000	●			●
38	× 38	4,000	●	●		●
40	× 40	4,000	●			●
42	× 42	4,000				●
45	× 45	4,000	●			●
50	× 50	4,000	●			●
55	× 55	4,000	●			●
60	× 60	4,000	●			●
65	× 65	4,000	●			●
70	× 70	4,000				●
75	× 75	4,000				●
90	× 90	4,000				●
100	× 100	4,000				●